

## Przykładowe zastosowania - możliwości urządzeń



Profile	ARKUS12		Bendo		PBT25		PBT35		HELIX	
	mm	min. Ø mm	mm	min. Ø mm	mm	min. Ø mm	mm	min. Ø mm	mm	min. Ø mm
	70/12	600	100/15	1600	120/15	2000	120/15	1200	200/30	4000
	100/10	300	200/15	600	300/15	600	260/20	700	260/30	900
	30/30	300	50/50	1000	60/60	1000	80/80	1400	100/100	2000
	30	300	50	1000	60	1000	80	1400	80	1000
	50/50/5	600	60/60/6	600	80/80/8	1200	100/100/10	1600	120/120/12	2000
	50/50/5	800	60/60/6	600	80/80/8	3000	100/100/10	2000	120/120/12	3000
	60/60/7	800	70/70/7	800	80/80/8	1000	100/100/10	1200	130/130/14	1500
	60/60/7	800	70/70/7	800	80/80/8	1000	100/100/10	1800	130/130/14	2000
	60/60/7	800	70/70/7	800	80/80/8	1000	100/100/10	1500	130/130/14	1500
	UNP 80	800	UNP 160	1200	UNP 180	1200	UNP 200	1200	UNP 260	2000
	UNP 80	800	UNP 160	1200	UNP 180	1200	UNP 200	1200	UNP 260	2000
			IPE 100	1600	IPE 120	1600	IPE 160	3000	HEA 200	6000
	I-PE 80	1000	IPE 140	1000	IPE 160	1000	IPE 180	1000	HEB 180	4000
	2" [60]	600	3" [88.9]	1000	4" [114]	1200	Ø 180	2000	Ø 219	4000
	50/50/3	600	120/40/4	2000	160/60/4	2000	100/100/10	1200	250/150/10	3500
	60/30/4	1000	120/40/4	2000	160/60/4	3000	160/60/4	2000	180/80/6	3500
			Steel	600	Steel	600	Steel	600		
			Steel	600	Steel	600	Steel	600		
			Steel	600	Steel	600	Steel	600		
	Aluminium	400	Aluminium	400	Aluminium	400	Aluminium	400		
	Aluminium	400	Aluminium	400	Aluminium	400	Aluminium	400		
			Aluminium	800	Aluminium	800	Aluminium	800		
	Aluminium	400	Aluminium	400	Aluminium	400	Aluminium	400		

\* niezbędne jest zastosowanie rolek specjalnych